

# 40" DUAL ROW LED LIGHTBAR WITH DAYTIME RUNNING LIGHT



CELEBRATING  
**70**  
YEARS  
OF INNOVATION



## HE-DRL40

# 40" DUAL ROW LED LIGHTBAR WITH DAYTIME RUNNING LIGHT



SALES 800-221-0932

### PRODUCT OVERVIEW

Heise's DRL Series dual-row lightbars have an integrated daytime running light in the center along the entire length of the bar, with a clean white light that provides additional visibility - day or night. The daytime running lights can be lit without the off-road lights being on and are powered by 6V to 24V circuits, using new 3-wire DT3 and ATP3 plugs and pigtails. Rated IP67 with a military grade metal breather port that allows moisture to escape. Built to last, featuring Heise's proprietary torture-tested heavy-duty construction with a virtually unbreakable polycarbonate lens, backed by a limited lifetime warranty.

#### Specifications:

- Input Voltage: 10-30V DC
- Power Consumption: 240W (40-3W white LEDs)
- Current Consumption: 17.4 amps @ 13.8 volts
- Raw Lumen: 18240 LM
- Lux @ 10m: 2531 (white LEDs only)
- Color Temperature: 6000K
- Beam Pattern: Combo flood (90 degree) / spot (8 degree)

#### Construction:

- Housing Material: Die-cast aluminum
- Housing Color: Black
- Lens Material: Polycarbonate
- Mounting Bracket: Die-cast aluminum
- Hole Dimensions: Brackets Turned Inward - 39.25"
- Brackets Turned Outward - 41.5"
- Mounting Bolt Drill - .25"
- Height of Lightbar: 3", Depth of Lightbar: 2.5", Length of Lightbar (without mounting brackets): 40"
- Electronics: Integrated-epoxy encapsulated
- Hardware: Stainless 316

#### Operation:

- Operating Temperature: -40 degrees C to +60 degrees C
- IP Rating: IP67
- Protections: Reverse Polarity

[www.HeiseLED.com](http://www.HeiseLED.com)

1-800-221-0932 | 386-257-1186

© COPYRIGHT 2018 METRA ELECTRONICS CORPORATION 12/18



#### WARNING:

Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).