

Fiat Family 2015-up*

*Visit AxxessInterfaces.com for up-to-date vehicle specific applications.

INTERFACE FEATURES

- “Plug & Play” harness for the AX-ADDCAM interface (sold separately)
- Reverse signal trigger generated via CAN bus communication of the vehicle
- Turn signal trigger generated via CAN bus communication of the vehicle
- (4) Programmable camera control wires (configured through the Axxess Updater program)

TOOLS REQUIRED

- Crimping tool and connectors, or solder gun, solder, and heat shrink
- Tape • Wire cutter • Zip ties

CONNECTIONS

- **For vehicles with a factory camera:** The camera signal will need to be interrupted and connected to the corresponding input/output RCA jacks on the AX-ADDCAM interface.
 - Connect the RCA jack from the AX-ADDCAM-CH6 labeled “Camera output”, to the RCA jack on the AX-ADDCAM interface labeled “Camera 1”.
 - Connect the RCA jack from the AX-ADDCAM-CH6 labeled “Camera input”, to the RCA jack on the AX-ADDCAM interface labeled “Camera output”.
- **For vehicles without a factory camera:**
 - Connect the RCA jack on the AX-ADDCAM-CH6 labeled “Camera input”, to the RCA jack on the AX-ADDCAM interface labeled “Camera output”.
 - Disregard the RCA jack labeled “Camera output”, it will not be used in this application.
 - Disregard the following (2) wires, they will not be used in this application: **Blue/Green** labeled “VSS input”, **Green/Red** labeled “VSS output”

ANALOG CONTROL TRIGGER WIRES

- The optional analog control wires can be activated with either a negative or positive trigger depending on how they are configured in the Axxess Updater program. These wires will only be used if manual control of the cameras will be desired. Otherwise tape off and disregard these wires.
 - Control 1 - **Gray/Blue** wire
 - Control 2 - **Gray/Red** wire
 - Control 3 - **Orange** wire
 - Control 4 - **Orange/White** wire

INSTALLATION

- Configure the AX-ADDCAM interface following the installation instructions included with the AX-ADDCAM interface. Failure to configure the interface will result in the interface not functioning properly.
- Remove the main harness from the factory radio, then install the AX-ADDCAM-CH6 in between.