



COMPONENTS

- AXDI-VW1 interface
- LD-AX-XSVI-VW1 harness

APPLICATIONS

Volkswagen

Beetle..... 2012-2015
CC..... 2009-2014
Eos..... 2006-2016

GLI 2008-2012
Golf 2002-2014
GTI 2002-2014
Jetta 2002-2015

Passat..... 2002-2015
Rabbit 2006-2009
Tiguan 2009-2015

Data Interface

Fits Select Volkswagen Models **2002-2016**

FEATURES

- Designed for non-amplified or analog amplified systems
- Provides accessory power (12-volt 10-amp)
- Retains R.A.P. (Retained Accessory Power)
- Provides NAV outputs (parking brake, reverse, speed sense)
- Pre-wired for Axxess SWC interface (sold separately)
- Retains balance & Fade
- Micro “B” USB updatable

TABLE OF CONTENTS

Connections: LD-AX-XSVI-VW1	2
Installation	3
Programming.....	3

Visit AxxessInterfaces.com for more detailed information about the product and up-to-date vehicle specific applications


TOOLS REQUIRED

- Crimping tool and connectors, or solder gun, solder, and heat shrink • Tape • Wire cutter
- Zip-ties

ATTENTION: With the key out of the ignition, disconnect the negative battery terminal before installing this product. Ensure that all installation connections, especially the air bag indicator lights, are plugged in before reconnecting the battery or cycling the ignition to test this product.

NOTE: Refer also to the instructions included with the aftermarket radio.

CONNECTIONS: LD-AX-XSVI-VW1



INSTALLATION

With the key in the off position:

1. Connect the **AXDI-VW1 harness** into the interface, and then to the wiring harness in the vehicle.

Note: The harness will connect to the harness removed from the disc drive located in the glove box for remote tuner applications.

2. If an **Axxess SWC Interface** (sold separately) will be used, do not connect it until the interface is programmed and fully functional.

PROGRAMMING

Attention! If the interface ever loses power, the following steps will need to be performed again. Please ensure that the owner of the vehicle knows this.

1. Turn the key (or push-to-start button) to the ignition position and wait until the radio comes on.

Note: If the radio doesn't come on within 60 seconds, turn the key to the off position, disconnect the interface, check all connections, reconnect the interface, and then try again.

2. Turn the key (or push-to-start button) to the off position, then to the accessory position. Test all functions of the installation for proper operation, before reassembling the dash.



AXDI-VW1

INSTALLATION INSTRUCTIONS



Having difficulties? We're here to help.



Contact our Tech Support line at:

386-257-1187



Or via email at:

techsupport@metra-autosound.com

Tech Support Hours (Eastern Standard Time)

Monday - Friday: 9:00 AM - 7:00 PM

Saturday: 10:00 AM - 5:00 PM

Sunday: 10:00 AM - 4:00 PM



**Metra recommends MECP
certified technicians**