



Fiat 500 Data Interface 2012-2015

INTERFACE FEATURES

- Provides accessory power (12-volt 10-amp)
- Retains R.A.P. (retained accessory power)
- Used in both amplified and non-amplified systems
- Provides NAV outputs (parking brake, reverse, speed sense)
- Pre-wired AXSWC harness (AXSWC sold separately)
- High level speaker input
- Retains OE BT/USB and 3.5mm audio
- Micro-B USB updatable

INTERFACE COMPONENTS

- AXVI-6515 Interface
- AXVI-6515 Harness

TABLE OF CONTENTS

Connections	2
Installation	3
Programming	3

TOOLS & INSTALLATION ACCESSORIES REQUIRED

- Crimping tool and connectors, or solder gun, solder, and heat shrink • Tape • Wire cutter
- Zip ties • Multimeter

Product Info



CONNECTIONS

From the AXVI-6515 harness to the aftermarket radio, connect the:

- **Yellow** wire to the radio's 12-volt battery or memory wire.
- **Black** wire to the radio's ground wire.
- **Red** wire to the ignition wire of the aftermarket radio
- **Orange** wire to the illumination wire. (if applicable)
- **Blue/White** wire to the radio's amp turn on wire.
- **White** wire to the left front positive speaker output.
- **White/Black** wire to the left front negative speaker output radio.
- **Gray** wire to the right front positive speaker output.
- **Gray/Black** wire to the right front negative speaker output.
- **Green** wire to the radio's left rear positive speaker output.
- **Green/Black** wire to the radio's left rear negative speaker output.
- **Purple** wire to the radio's right rear positive speaker output.
- **Purple/Black** wire to the radio's right rear negative speaker output.

The following (3) wires are only for multimedia/navigation radios that require these wires.

- **Light Green** wire to the parking brake wire of the aftermarket navigation radio.
- **Blue/Pink** wire to the VSS or speed sense wire of the aftermarket navigation radio.
- **Green/Purple** wire to the reverse wire of the aftermarket navigation radio.
- Plug the AUX/3.5mm or BT/USB RCAs to the aftermarket radio's audio AUX input.

12-pin AXSWC harness & 3.5mm jack:

The 12-pin **AXSWC** harness & 3.5mm jack is to be used with the **AXSWC** (sold separately) to retain steering wheel audio controls. If the **AXSWC** is not being used, disregard this harness. If it is to be used, refer to the **AXSWC** instructions for radio connections and programming. Disregard the harness that comes with the **AXSWC**.

INSTALLATION

With the key in the off position:

- Connect the **AXVI-6515 harness** to **AXVI-6515 interface**, and then to the wiring harness in the vehicle.

Note: If using the AXSWC, connect it after you program and test the AXVI-6515, with the key in the off position.

PROGRAMMING

Attention! If the interface loses power for any reason, the following steps will need to be performed again.

- Turn the key (or push-to-start button) to the ignition position and wait until the radio comes on.

Note: If the radio does not come on within 60 seconds, turn the key to the off position, disconnect the interface, check all connections, reconnect the interface, and then try again.

- Turn the key to the off position, and then to the accessory position. Test the interface/radio for proper operation.



AXVI-6515

INSTALLATION INSTRUCTIONS

Having difficulties? We're here to help.



Contact our Tech Support line at:

386-257-1187



Or via email at:

techsupport@metra-autosound.com

Tech Support Hours (Eastern Standard Time)

Monday - Friday: 9:00 AM - 7:00 PM

Saturday: 10:00 AM - 7:00 PM

Sunday: 10:00 AM - 4:00 PM



KNOWLEDGE IS POWER

Enhance your installation and fabrication skills by enrolling in the most recognized and respected mobile electronics school in our industry. Log onto www.installerinstitute.com or call 800-354-6782 for more information and take steps toward a better tomorrow.



**Metra recommends MECP
certified technicians**