

**XSVI-5520-NAV****Ford accessory and NAV output CAN harness 2007-up**

- Provides accessory (12 volt 10 amp)
- Retains R.A.P. (retained accessory power)
- Used in non-amplified systems, or when replacing amplified system
- Provides NAV outputs (parking brake, reverse, and V.S.S.)
- Prewired ASWC-1 harness included (ASWC-1 sold separately)
- High level speaker input
- USB updatable

**APPLICATIONS****FORD**

Edge	2007-2010
Escape	2008-2012
Expedition	2007-up
Flex	2008-2012
Focus	2008-2011
Fusion	2010-2012
F-150	2009-2012
F150 STX/FX2 base/XLT base	2013
F150 STX/XLT base	2014
F250/350/450/550	2008-2012
F250/350/450/550 (XL/XLT)	2013-up
Mustang	2009-up
Taurus	2010-2012

**LINCOLN**

MKX	2007-2010
MKZ	2007-2009
Navigator	2007-up
<i>(only to be used when replacing an amplified system)</i>	

**MAZDA**

Tribute	2008-2011
---------	-----------

**MERCURY**

Mariner	2008-2011
Milan	2010-2011

**WIRING UP THE XSVI-5520-NAV**

- Connect the **Yellow** wire to the radio's 12 volt battery or memory wire.
- Connect the **Black** wire to the radio's ground wire.
- Connect the **Red** wire to the ignition wire of the aftermarket radio.
- Connect the **Orange** wire to the illumination wire of the aftermarket radio. If the aftermarket radio has no illumination wire, tape off the orange wire.
- Connect the **Blue** wire to the antenna turn on wire of the aftermarket radio.

**1-800-221-0932****metraonline.com**



- Connect the **White** wire to the left front positive speaker output of the aftermarket radio.
- Connect the **White/Black** wire to the left front negative speaker output of the aftermarket radio.
- Connect the **Gray** wire to the right front positive speaker output of the aftermarket radio.
- Connect the **Gray/Black** wire to the right front negative speaker output of the aftermarket radio.
- Connect the **Green** wire to the radio's left rear positive speaker output.
- Connect the **Green/Black** wire to the radio's left rear negative speaker output.
- Connect the **Purple** wire to the radio's right rear positive speaker output.
- Connect the **Purple/Black** wire to the radio's right rear negative speaker output.

The following wires are for the aftermarket radios that have navigation built in.

- Connect the **Light Green** wire to the parking brake wire of the aftermarket navigation radio (if applicable).
- Connect the **Blue/Pink** wire to the VSS or speed sense wire of the aftermarket navigation radio (if applicable).
- Connect the **Green/Purple** wire to the reverse wire of the aftermarket navigation radio (if applicable).
- Cycle the key by turning the ignition on for 30 seconds, then "off" and "on" again to test the radio.

### ASWC-1 (if installing)

After the XSVI is initialized, plug in the ASWC into the 12 pin harness of the XSVI-5520-NAV and refer to the ASWC instructions.



#### KNOWLEDGE IS POWER

Enhance your installation and fabrication skills by enrolling in the most recognized and respected mobile electronics school in our industry. Log onto [www.installerinstitute.com](http://www.installerinstitute.com) or call 800-354-6782 for more information and take steps toward a better tomorrow.



Metra recommends MECP certified technicians

**Caution:** Metra recommends disconnecting the negative battery terminal before beginning any installation. All accessories, switches, and especially air bag indicator lights must be plugged in before reconnecting the battery or cycling the ignition.

**Note:** Refer to the instructions included with the aftermarket radio.



1-800-221-0932



[metraonline.com](http://metraonline.com)